



# Combi Drill LXT®

## DHP482Z

18V • 62 Nm • 0 – 1 900 min<sup>-1</sup>

**Powerful general-use combi drill with hammer action for professionals**

An efficient drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 62 / 36 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Tool only, battery and charger not included.



**LXT**

### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 600 / 1900 min <sup>-1</sup>
Max. fastening torque Hard/Soft	62 / 36 Nm
Torque setting	21
Max Torque	64 Nm
Impacts per Minute (IPM)	0 - 9000 / 28500 min <sup>-1</sup>
Drilling Capacity Wood (Auger Bit)	38 mm
Drilling Capacity Wood (Self-feed bit)	51 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Concrete	13 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Flat bit	38 mm
Drilling Capacity Hole Saw	51 mm
Driving Shank	1/2"-20UNF "

### User benefits

- Highly efficient and compact machine for professional use
- Battery protection system automatically shuts off power when the battery level is low
- Optimal handle design
- LED light illuminates the work site
- Ergonomic handle for easy manoeuvring

**EAN 0088381699051**

Link to product - [www.makitauk.com](http://www.makitauk.com)



# Related products

Standard AC

346317-0

Belt Hook



Optional AC

196311-0

Keyless Drill Chuck, 13 mm



251314-2

Truss Head Screw M4\*12, Td140D



346317-0

Belt Hook



D-72877

Drill bit set T.C.T, 5 pcs



Other

User manual

Parts drawing